



# Shenandoah

## ☞ SPECIFICATIONS

<b>Style Number:</b>	SHE40204
<b>Plank Size:</b>	7.17" x 48.03"
<b>Overall Thickness:</b>	5.0 mm
<b>Product Construction:</b>	4.0 mm Rigidcore + 1.0 mm MaxStepPro™
<b>Wear Layer:</b>	20 mil with MaxProtect®
<b>Edge:</b>	ColorEdge®
<b>Gloss Level:</b>	Matte
<b>Installation Method:</b>	i4F Triple-Lock® Click4U®
<b>Recycled Content:</b>	None
<b>Certifications:</b>	GreenGuard Gold®

<b>Classification</b>	<b>ASTM F3261-20</b>	Class I, Type B, Grade 2, Backing Class B
<b>Chemical Resistance</b>	<b>ASTM F 925</b>	Passes
<b>Critical Radiant Flux</b>	<b>ASTM E 648-06</b>	Passes
<b>Dimensional Stability</b>	<b>ASTM F 2199</b>	Passes
<b>Residual Indentation</b>	<b>ASTM F 1914</b>	Passes
<b>Resistance to Heat</b>	<b>ASTM F 1514</b>	Passes
<b>Resistance to Light</b>	<b>ASTM F 1515</b>	Passes
<b>Smoke Density</b>	<b>ASTM E 662</b>	Passes
<b>Thickness w/ Foam Layer</b>	<b>ASTM F 387</b>	5.0 mm
<b>Thickness, Wearlayer</b>	<b>ASTM F410</b>	.5 mm
<b>Size Tolerance</b>	<b>ASTM F2055</b>	Passes
<b>Flatness</b>	<b>ISO 24337</b>	Passes
<b>Openings</b>	<b>ISO 24337</b>	Passes
<b>Ledging</b>	<b>ISO 24337</b>	Passes
<b>Static Load</b>	<b>ASTM F970</b>	Passes

## ☞ PACKAGING

<b>Square Feet Per Carton:</b>	23.90	<b>Pieces Per Carton:</b>	10
<b>Square Feet Per Pallet:</b>	1,553.50	<b>Cartons Per Pallet:</b>	65
<b>Square Feet Per Container:</b>	31,070	<b>Pallets Per Container:</b>	20
<b>Weight Per Carton:</b>	34.72 lbs	<b>Weight Per Pallet:</b>	2,256.80 lbs

## ☞ COLOR LINE

50001 Alder	50054 Cortland	50105 Rupert	50137 Pax
50002 Bingham	50056 Dryfork	50115 Slaty Fork	50138 Garten

## ☞ WARRANTIES

Lifetime Limited Waterproof*	20 Year Limited Residential Wear*	5 Year Light Commercial Wear*
------------------------------	-----------------------------------	-------------------------------

\*Please visit our website for full warranty details.